

In the Specification

Kindly replace paragraphs [0001] through [0011] with the following:

Related Application

This is a §371 of International Application No. PCT/FR2005/000553, with an international filing date of March 8, 2005 (WO 2005/088902, published September 22, 2005), which is based on French Patent Application No. 04/50463, filed March 8, 2004.

Technical Field

~~The present invention~~This disclosure relates to the area of binary data from transformations applied to digital texts.

~~The present invention proposes to supply a system that permits the protection and the distribution in a secure manner of compressed digital texts and the restitution of the original digital text while preventing a non-authorized use of or access to these compressed digital texts.~~

~~In the following the term “text” defines a succession of characters from an alphabet of letters or numbers and of punctuation signs.~~

~~In the following the term “digital text” defines the succession of bytes representing characters from an alphabet and/or punctuation signs and/or data for formatting and displaying a text on a viewing screen.~~

~~In the following the term “compressed digital text” defines the binary data stream from an algorithm of statistical compression applied to the digital text.~~

~~In the following the action of displaying a compressed digital text is defined as the series of operations consisting in reading and decoding the succession of binary data that constitutes the compressed digital text for restituting the text on a viewing screen in order that it can be read and understood from a semantic viewpoint by a human being.~~

~~The present invention relates more particularly to an apparatus capable of transmitting in a secure manner a set of compressed digital texts to a viewing screen and/or for being recorded on the hard disk of a computer or on the recording support of a box connecting the telecommunication network to a viewing screen such as a television screen or a personal computer monitor while avoiding any fraudulent use such as the possibility of making illicit copies of textual contents or of compressed digital texts. The invention also relates to a client-server system between the server that furnishes the secure compressed digital texts and the client that displays, reads, records or prints the compressed digital texts.~~

Background

It is possible with the current solutions to transmit voluminous texts and documents in digital form via telecommunication networks of the cable, DSL (Digital Subscriber Line) or BLR (Local Radio Loop ~~{B=FR boucle=loop}~~) type. Furthermore, ~~in order to~~ avoid the pirating of works and confidential documents broadcast in this manner, the latter are frequently encrypted or scrambled by various well known ~~means well known to an expert in the art.~~

As concerns the secure distribution of texts and binary data, ~~the prior art contains the document WO9805142 "Multi-Matrix Encryption for Private Transmission of Data" presenting WO 98/05142 discloses~~ a process and equipment for the protection of data and their secure transmission through an electronic network. The document concerns the encryption of textual data with the aid of matrices of ASCII characters generated by keys. The three key elements at the input are a PIN code (Personal Identification Number), the number of the bank account of the user and a password. These three keys initiate the generation of a matrix A and ~~[[of]]~~ a matrix B. Matrices A and B are generated in a pseudorandom manner with the aid of an analytic function such as a logarithmic function, a trigonometric function, a square root function or the like. The distribution of ~~[[the]]~~

characters in matrices A and B is irregular and each character is unique. Three integrity control values are calculated and incorporated in the protected stream, one of which represents the sum of the input textual data and the two others are relative to the three input key elements. The input data is transformed into a decimal value with four numbers by operations of permutation, addition, subtraction, multiplication, division and they are then divided into two values of two numbers. These two values are indexed relative to the elements of matrices A and B ~~in order~~ to form the stream of protected data. However, due to the division into two parts for the indexation, the size of the protected stream increases considerably relative to the size of the initial data. Moreover, all the protected data, as well as the three control values generated, are present in the protected data. Therefore, ~~this prior art~~ WO '142 does not correspond to the criteria of high security, ~~the goal of the present invention.~~

Summary

This disclosure relates a process for secure distribution of compressed digital texts formed by blocks of binary data stemming from digital transformations applied to an original text including modifying at least one binary data in one of the blocks according to at least one substitution operation including extracting the binary data in a block and replacing it with a decoy, transmitting a modified compressed digital text in conformity with a format of the original compressed digital text including modified blocks, transmitting by a separate path the modified compressed digital text and digital complementary information, and reconstituting the original compressed digital text by a calculation on equipment of an addresses as a function of the modified compressed digital text and of the complementary information.

This disclosure also relates a system for implementing the process for secure distribution of compressed digital texts including at least one server containing original compressed digital texts, an

apparatus for analyzing the compressed digital text, an apparatus for separating the original compressed digital text into a modified compressed digital text and into complementary information as a function of the analysis, at least one telecommunication network for transmitting, and at least one apparatus in equipment of an addressee for recomposition of the original compressed digital text as a function of the modified compressed digital text and the complementary information.

Brief Description of the Drawing

The disclosure will be better understood with the aid of the description, given below purely by way of explanation, of one aspect of the system with reference made to attached Fig. 1, that illustrates a particular aspect of the system permitting the protection and distribution in a secure manner of compressed digital texts.

Detailed Description

We supply a system that permits the protection and the distribution in a secure manner of compressed digital texts and the restitution of the original digital text while preventing a non-authorized use of or access to these compressed digital texts.

The term “text” defines a succession of characters from an alphabet of letters or numbers and of punctuation signs.

The term “digital text” defines the succession of bytes representing characters from an alphabet and/or punctuation signs and/or data for formatting and displaying a text on a viewing screen.

The term “compressed digital text” defines the binary data stream from an algorithm of statistical compression applied to the digital text.

The action of displaying a compressed digital text is defined as the series of operations including reading and decoding the succession of binary data that constitutes the compressed digital

text for restituting the text on a viewing screen such that it can be read and understood from a semantic viewpoint by a human being.

In particular, we provide an apparatus capable of transmitting in a secure manner a set of compressed digital texts to a viewing screen and/or for being recorded on the hard disk of a computer or on the recording support of a box connecting the telecommunication network to a viewing screen such as a television screen or a personal computer monitor while avoiding any fraudulent use such as the possibility of making illicit copies of textual contents or of compressed digital texts. The invention also relates to a client-server system between the server that furnishes the secure compressed digital texts and the client that displays, reads, records or prints the compressed digital texts.

The protection of compressed digital texts ~~realized in a manner in conformity with the present invention~~ is based on the ~~principle of the~~ principle of the deletion and the replacement of certain information coding the original compressed digital texts by any method, e.g.: ~~Substitution~~, substitution, modification, permutation or shifting of the information. This protection is also based on a knowledge of the structure of the binary data at the output of the encoder producing the compressed digital texts.

~~The present invention concerns~~ We address the general principle of a process for securing compressed digital texts. The solution ~~consists in~~ includes extracting and permanently preserving, in a location that cannot be accessed by the user, in fact, in the distribution network, a part of the compressed digital text recorded at the client's or sent online, which part is of prime importance for exploiting ~~this~~ the compressed digital text on a display screen, but has a very low volume relative to the total volume of the compressed digital text recorded at the user's or received online. The lacking part will be transmitted via the distribution network at the moment of the exploitation of ~~this~~ the compressed digital text.

Kindly replace paragraphs [0013] through [0023] with the following:

~~In order to~~To implement the process ~~the invention realizes,~~ we provide a protection system comprising an analysis and protection module and a recomposition module that are based on a digital format stemming from the encoding of a digital text using statistical compression algorithms. The analysis and protection module ~~proposed by the invention~~ is based on the substitution by “decoys” or on the modification of part of the binary data composing the original compressed digital text. The fact of having removed and substituted a part of the original data of the original compressed digital text during the generation of the modified compressed digital text does not permit the recomposition of ~~this~~the original compressed digital text from only the data of ~~this~~the modified compressed digital text.

Based on the characteristics of the compressed digital text, several variants of the protection process are implemented and ~~are illustrated with the exemplary embodiments~~selected examples.

~~The present invention relates~~We more particularly ~~[[to]]~~provide an apparatus capable of transmitting in a secure manner a digital text to a display device and/or for being recorded in the memory of the backup apparatus of a box connecting the telecommunication network to the display device while preserving the semantic content of the text, but avoiding the possibility that the digital text could be read and copied illicitly.

A compressed digital text generated by a statistical compression algorithm from a digital text is constituted ~~[[by]]~~of a succession of binary data representing codes and or entries in coding tables and/or pointers to the positions in the digital text.

~~The present invention consists~~process includes, after ~~the~~ analysis of the compressed digital text, ~~[[in]]~~ extracting at least one original binary data in the compressed digital text, which original binary data represents a code or an entry in a coding table or a pointer, which data is randomly

selected, and in replacing it by a binary data called a decoy of the same size and of the same nature, but with a random value ~~in order~~ to generate a compressed digital text in conformity with the format of the original compressed digital text. The displaying of the modified compressed digital text then restores a text that is illegible and/or incomprehensible from a semantic viewpoint for a human being.

~~According to a variant of the invention the~~The original binary data to be extracted ~~[[is]]~~may be selected in a deterministic manner.

~~According to another variant of the invention the~~The value of the decoy binary data ~~[[is]]~~may be calculated in a deterministic manner.

~~According to another variant of the invention the~~The decoy binary data ~~has~~may have a size different from the size of the original binary data.

~~The invention concerns according to its most general meaning a process for~~thus relates to the secure distribution of compressed digital texts formed by blocks of binary data stemming from digital transformations of applied to an original text, characterized in that it comprises:

[[-]] [[A]] ~~a preparatory stage consisting including~~ modifying at least one binary data in one of the ~~[[se]]~~ blocks according to at least one substitution operation ~~consisting of~~ the including extraction of ~~this~~the binary data in a block and its replacement by a decoy,

[[-]] [[A]] a transmission stage:

- i. [[Of]] of a modified compressed digital text in conformity with the format of the original compressed digital text, constituted ~~[[by]]~~of blocks modified during the course of the preparatory stage, and
- ii. [[By]] by a separate path of ~~this~~the modified compressed digital text, of digital complementary information permitting ~~the~~ reconstitution of the original compressed

digital text from the calculation on the equipment of the addressee as a function of
~~this~~the modified compressed digital text and ~~of this~~the complementary information.

~~In an embodiment this~~The binary data may represent ~~[[s]]~~ an entry into a coding table and the
decoy represents a different entry into ~~this~~the coding table.

~~In another embodiment the~~The coding table ~~[[is]]~~may be constructed in a dynamic manner
during the decoding.

Kindly replace paragraphs [0025] through [0029] with the following:

~~This~~The binary data advantageously represents a prior position in the digital text generated in
the course of the decoding and the decoy represents a different prior position in ~~this~~the digital text
generated in the course of the decoding.

~~In an embodiment the~~ modified compressed digital text 5 ~~[[is]]~~may be in conformity with the
standard of the original compressed digital text 1.

~~In another embodiment the~~The modified compressed digital text 5 ~~[[is]]~~may be in conformity
with the format of the original compressed digital text 1.

~~In an embodiment this~~The binary data and ~~this~~the decoy may have the same size.

~~In another embodiment this~~The binary data and ~~this~~the decoy may have different sizes.

Kindly replace paragraphs [0031] through [0032] with the following:

~~In a variant the~~The modified compressed digital text ~~has~~may have the same size as the
original compressed digital text.

~~In another variant the~~The modified compressed digital text ~~has~~may have a size different than
that of the original compressed digital text.

Kindly replace paragraphs [0039] through [0040] with the following:

~~The present invention~~We also relates to provide a system for implementing the process, comprising at least one server containing original compressed digital texts and comprising an apparatus for analyzing the compressed digital text, an apparatus for separating the original compressed digital text into a modified compressed digital text and into complementary information as a function of ~~this~~the analysis, at least one telecommunication network for the transmission and at least one apparatus in the equipment of the addressee for the recomposition of the original compressed digital text as a function of ~~this~~the modified compressed digital text and ~~of this~~the complementary information.

~~The present invention~~systems and processes will be better understood with the aid of the following ~~exemplary embodiments~~examples concerning statistical compression algorithms of digital texts well known to an expert in the art.

Kindly replace paragraph [0042] with the following:

The data stemming from the LZW compression algorithm ~~consists of~~includes a sequence of codes that have a length comprised between 9 and 12 bits. Each code represents either a simple character (that is, a byte comprised between 0 and 255), a table re-initialization marker (value 256), an “end of data” marker (value 257) or also an entry into a table (value > 258), which entry is associated with a sequence of bytes found previously in the digital text to be compressed. Initially and in the encoding as well as in the decoding the codes have a length of 9 bits (value comprised between 0 and 257) and the table is initialized with the 258 first entries (the 256 values of a byte + the re-initialization marker 256 + the end of data marker 257).

As the encoding (or decoding) process progresses, new codes are added to the table, each associated with sequences of bytes with variable lengths that can appear in a recurrent manner in the

digital text to be compressed (or decompressed). Each time that a byte sequence that has already appeared reappears in the digital text the code corresponding to the entry of the table storing this same sequence is sent to the compressed digital text. Likewise, during decompression, the codes are systematically replaced by the byte sequence read at the corresponding entry of the table and a new entry is added to the table ~~in order~~ to store the sequence formed from the previously decoded sequence. Thus, the table is constructed dynamically in the same manner in the encoding as in the decoding.

When the binary length of the codes is no longer sufficient for representing an entry in the table, it is increased by 1: Thus, as soon as the number of entries in the table reaches 510, the codes are coded on 10 bits (and in the same manner when the entry number reaches 1022 (11 bits) and 2046 (12 bits). However, the codes never exceed a length of 12 bits (4095 entries maximum). In a compressed digital text the code 256 can appear several times: The table is then re-initialized and the binary length of the codes re-initialized to 9.

Kindly replace paragraphs [0044] through [0048] with the following:

The protection operation of an LZW compressed digital text ~~consists~~ includes extracting in a random and/or deterministic manner in the sequence one or several (this number is determined in a random or calculated manner) original codes and in replacing them by one or several valid “decoy” codes, which valid “decoy” codes point to entries in the table. A “decoy” code is called valid when the new pointed entry in the table exists and then ~~this~~ the entry corresponds to a sequence of bytes with a length identical to that pointed by the original code.

The digital text decompressed from the modified compressed digital text has the same size as the original digital text. The text displayed from the modified compressed digital text ~~consists~~

~~of~~includes a random succession of alphabetical characters and punctuation signs that is not intelligible to a human being.

The Adobe PDF (Portable Document Format) format uses the LZW statistical compression algorithm for compressing objects of the digital text type in a document encoded in the PDF format. An object of the digital text type represents a paragraph, one or several pages of text, the legend of a figure. Each object of the digital text typed is coded in an independent manner. Thus, the ~~present invention~~process allows the protection of certain digital texts ~~in order~~ to render the displayed text illegible and/or incomprehensible while leaving other texts objects in the same PDF document readable and comprehensible.

The ~~present invention~~process permits the protection of objects of the figure ~~type and of the~~ digital image type incorporated in a text document and stemming from a statistical compression algorithm by making them incoherent from the viewpoint of human visual perception while leaving text objects in the same PDF document readable and comprehensible.

The ~~present invention~~process advantageously permits the protection of digital images in the TIFF and GIF formats by making them incoherent from the viewpoint of human visual perception.

Kindly replace paragraphs [0050] through [0051] with the following:

The Huffman algorithm ~~consists~~includes replacing a succession of symbols in an original stream and stemming from a certain alphabet by a series of codes with variable lengths, each code substituting a symbol in the compressed stream. The algorithm begins by analyzing the number and ~~the~~ frequency of the symbols appearing in the original stream ~~in order~~ to construct a coding tree from which it associates each encountered symbol with a code with a length inversely proportional to the frequency of the appearance of the symbol in the original stream. The compression then ~~consists in~~ replacing~~replaces~~ each symbol with its associated code. However, the decompression algorithm

needs the coding tree ~~in order~~ to decompress the compressed stream. However, a modified version of Huffman is used for the zlib/deflate algorithm: The coding tree is constructed respecting the supplementary rules that confer a property of unicity to it and the decompression algorithm no longer needs the coding tree, but only the lengths of the codes used ~~in order~~ to reconstruct the latter.

Algorithm LZ77 identifies the sequences of recurrent data in a stream in a sliding window of fixed size. When a sequence that has already appeared is detected again, it is replaced in the compressed stream by two numbers: A distance d and a length l . The distance indicates at which location in the window ~~this~~the same sequence begins and the length indicates how much data the identified sequence comprises. During the decompression, each time the algorithm encounters a couple (d, l) it recopies in the exiting stream the sequence of data with length l read from the current position less d .

Kindly replace paragraph [0054] with the following:

~~In conformity with the invention the~~The operation for protecting a compressed digital text according to the zlib/deflate algorithm ~~consists~~includes modifying one or several blocks coded according to modes 2 or 3. The modifications ~~consist~~include extracting from the compressed digital text a Huffman code coding a symbol of the “character” or distance d type and replacing it with a valid Huffman code. A Huffman code is called valid if it has the same length as the code that it replaces and if it corresponds effectively to a coded symbol of the same type, that is, character or distance.

Kindly replace paragraph [0056] through [0057] with the following:

~~The displaying of~~Displaying the modified digital text produces a text that is illegible and/or incomprehensible for a human being because it displays a succession of characters and punctuation signs with no logic.

The specifications of the zlib format define a field of 4 bytes ADLER32 located at the end of the compressed digital texts: This field stores a unique identifier of the original digital text and it is used during the decompression ~~in order~~ to verify the integrity of the digital text. In the case of a compressed and modified zlib/deflate digital text, ~~compressed and modified according to our invention~~ the signature of the decompressed digital text will not be identical to that of the original digital text.

Kindly replace paragraphs [0059] through [0060] with the following:

~~The invention will be better understood with the aid of the description, given below purely by way of explanation, of an embodiment of the invention with reference made to attached figure 1, that illustrates a particular embodiment of the system permitting the protection and distribution in a secure manner of compressed digital texts in accordance with the invention.~~

~~Compressed~~Turning now to Fig. 1, digital text 1 to be secured is passed via link 2 to analysis and protection module 3 that generates a modified compressed digital text 5 in a format identical to original compressed digital text 1 except that certain binary data have been replaced by values different than the original ones, and is stored in server 6. The complementary information 4 of any format is also placed in server 6 and contains information relative to the data of the compressed digital text that was modified, replaced, substituted or shifted, and to its values or emplacements in the original compressed digital text.

Kindly replace paragraph [0063] with the following:

Or, server 6 decides that user 8 has the rights to correctly display the compressed digital text. In ~~this~~that case, synthesis module 13 makes a display request to server 6 containing complementary information 4 necessary for the recomposition of the original compressed digital text 1. Server 6 then sends complementary information 4 via telecommunication network 7 of the analog or digital

telephone line type, DSL (Digital Subscriber Line) or BLR (Loop Local Radio) type, via DAB networks (Digital Audio Broadcasting) or via digital mobile telecommunication networks (GSM, GPRS, UMTS) 7, which complementary information permits the reconstitution of the compressed digital text in such a manner that user 8 can store it in buffer memory 12. Synthesis module 13 then proceeds to the reconstitution of the original compressed digital text from the modified compressed digital text that it reads in its reading buffer memory 11, and modified fields, whose positions it knows, as well as the original values are restored by virtue of the content of the complementary information read in recomposition buffer memory 12. Complementary information 4 that is sent to the recomposition module is specific for each user and is a function of his rights, e.g., single or multiple use, the right to make one or several private copies, late or early payment.

Kindly replace paragraph [0066] with the following:

Complementary information 4 is advantageously recorded on a physical support 7bis with a credit card format constituted [[by]] of a smart card or a flash memory card. This card 7bis is then read by module 12 of the apparatus 8 comprising a card reader 7ter.